

The background of the top half of the page features a close-up of a person's face, partially obscured by a semi-transparent purple overlay. To the right, a pressure gauge is visible with numerical markings such as 500, 700, and 760. The overall color palette is dominated by purple and teal tones.

EXPERTISE THROUGH EXPERIENCE



INSTRUMENTS CORPORATION

VEEGO a trusted name in Chemical, Pharmaceutical, Petrochemical Industries for quality instruments. The company was established in the year 1976 to design and manufacture scientific analytical instruments for research development and quality control laboratories.

Main objective of the company is to cater requirement of local industries, offer them simple, compact, reliable and easy to operate instruments. Pioneering experience in the field of sophisticated instruments, a team of highly experienced instrumentation, electrical engineers, software professionals and chemists form a strong back bone of the company.

Strong technical support and excellent customer relationship contributed to quick growth. During these three decades 'VEEGO' products have gained good reputation for reliability, accuracy and simplicity.

'VEEGO' products are known to almost all industries in India. To promote overseas business, Progressive Instruments started exports of 'VEEGO' products. Over 35 years we pride ourselves as leading manufacturer of wide range of scientific instruments and equipment.



VEEGO

OUR MISSION

To offer range of instruments having:

- Excellent Reliability.
- Good Quality.
- Ingenious Simplicity.
- Competitive Price.

QUALITY ASSURANCE

Management experts, highly qualified and experienced professional staff are the strong support to quality management system.

Our dedicated team guarantee the performance of each and every instrument we manufacture.

CUSTOMER CARE

We are committed to

- Understand Customer Requirements.
- Offer best service.
- On-Time delivery.
- Provide Technical support.

PRODUCTS OF PROGRESSIVE INSTRUMENTS

Tablet Dissolution Tester

Tablet Disintegration Tester

Tablet Friability Tester

Tablet Hardness Tester

Tap/Bulk Density Tester

Leak Test Apparatus

TABLET DISINTEGRATION TEST APPARATUS

The disintegration tester measures time required under a given set of conditions for tablets to disintegrate into particles. Generally, this test is useful as a quality assurance tool for conventional dosage forms.

VTD-D/VTD-DV/VTD-AV/VTD-DVP/VTD-AVP/VTD-4DV

COMMON FEATURES:

- Two Baskets as per IP/BP/USP Standards are supplied.
- Microcontroller based circuit to control the temperature of water bath.
- PT-100 Sensor for sensing the temperature.
- Optically isolated solid state latch for water bath.
- User friendly and easy to operate 4 X 4 matrix key board.
- Non volatile memory.
- Pause facility: This feature enables the operator to check Disintegration state of the tablets and continue the test without disturbing test parameters.
- All models of Disintegration Test Apparatus meet International Standards with respect to Calibration, Validation and IQ, OQ requirements.

SPECIFICATIONS:

- Number of Strokes : 30 Strokes/min.
- Temperature Range : 30.0°C to 40.0°C
- Timer : Settable from 1 min to 240 min.
- Heater : 750 watt
- Power consumption: 230V, 50Hz, 1.2KW (approx.)

OPTIONAL ACCESSORIES:

- Bolus basket with three tubes.
- Bolus basket with single large tube.

VTD-D

- Economical digital Tablet Disintegration Test Apparatus.
- Informative 4 line LCD screen to display messages.
- Sturdy motor for constant speed of DT strokes.

Photography of Accessories on pg. 18

DIGITAL ADVANCED TABLET FRIABILITY TEST APPARATUS WITH VALIDATION FACILITY

This instrument simulates environment, tablets are subjected to during manufacturing, packaging and distribution process. It is used to determine durability and abrasiveness of tablets.



VFT-DV

- Latest Microcontroller based circuitry.
- Two line Alpha-Numeric display.
- User friendly key board for data entry.
- 2 drums front loading system.
- Interlocking mechanism to ensure correct drum position.
- Tablets can be inserted in the drums, with out detaching the drums from the assembly.
- Facility for abrasion and friability drums.

- 10° tilt facility.
- Validation facility.
- Parallel port printer and balance interface.

Photography of Accessories on pg. 18