





OUR MISSION

To offer range of instruments having:

- Excellent Reliability.
- Good Quality.
- Ingenious Simplicity.
- Competitive Price.

QUALITY ASSURANCE

Management experts, highly qualified and experienced professional staff are the strong support to quality management system.

Our dedicated team guarantee the performance of each and every instrument we manufacture.

CUSTOMER CARE

We are committed to

- Understand Customer Requirements.
- Offer best service.
- On-Time delivery.
- Provide Technical support.

PRODUCTS OF PROGRESSIVE INSTRUMENTS

Tablet Dissolution Tester

Tablet Disintegration Tester

Tablet Friability Tester

Tablet Hardness Tester

Tap/Bulk Density Tester

Leak Test Apparatus

TABLET DISINTEGRATION TEST APPARATUS

The disintegration tester measures time required under a given set of conditions for tablets to disintegrate into particles. Generally, this test is useful as a quality assurance tool for conventional dosage forms.

VTD-D/VTD-DV/VTD-AV/VTD-DVP/VTD-AVP/VTD-4DV

COMMON FEATURES:

- Two Baskets as per IP/BP/USP Standards are supplied.
- Microcontroller based circuit to control the temperature of water bath.
- PT-100 Sensor for sensing the temperature.
- Optically isolated solid state latch for water bath.
- User friendly and easy to operate 4 X 4 matrix key board.
- Non volatile memory.
- Pause facility: This feature enables the operator to check Disintegration state of the tablets and continue the test without disturbing test parameters.
- All models of Disintegration Test Apparatus meet International Standards with respect to Calibration, Validation and IQ, OQ requirements.

SPECIFICATIONS:

• Number of Strokes : 30 Strokes/min.

• Temperature Range: 30.0°C to 40.0°C

• Timer : Settable from

I min to 240 min.

• Heater : 750 watt

• Power consumption: 230V, 50Hz, I.2KW

(approx.)

OPTIONAL ACCESSORIES:

- · Bolus basket with three tubes.
- Bolus basket with single large tube.

VTD-D

- Economical digital Tablet Disintegration Test Apparatus.
- Informative 4 line LCD screen to display messages.
- Sturdy motor for constant speed of DT strokes.

Photography of Accessories on pg. 18

DISINTEGRATION TESTER

FOR SUPPOSITORY TABLETS

The disintegration tester determines whether suppositories soften or disintegrate within a prescribed time when placed in an immersion fluid under experimental conditions.



VTS-2

- Designed for the measurement of disintegra tion time of pessaries and suppositories.
- LCD display screen to indicate test parameters.
- Automatic rotation through 180 degree and selectable cycle time.
- Built-in circulation pump to maintain the Temperature between 36.0°- 37.0°C.
- Three samples are tested at the same time.
- The instrument meets requirements of the pharmacopoeias.

VTS-P

Test for both Suppository & Peccaries can be conducted on this combined system.

Instrument same as Model: VTS-2 with additional features like:

Attachment to test Disintegration Test Time of Peccaries.

All instruments work on 230 volts A.C. supply. Supplementary components to support other supply voltages available on request.

Photography of Accessories on pg. 18